



1. WHERE THERE IS AN ADJACENT FOOTPATH, ENSURE BENCH SEAT FACES FOOTPATH AND THE CONCRETE SLAB MATCHES COLOUR AND FINISH.
2. WHERE SLAB IS ADJACENT TO A FOOTPATH THERE IS TO BE AN OVERALL TYPICAL FALL OF 1:50 ACROSS BOTH SURFACES.
3. REFER TO ENGINEERING STANDARD DETAIL EDCM-401 FOR CONCRETE JOINTS DETAIL.
4. WHERE SURROUNDING SURFACE IS GRAVEL SURFACE IS GRAVEL, PROVIDE CONCRETE FOOTING AS PER MANUFACTURERS SPECIFICATIONS AND CONCEAL 30MM BELOW THE AGGREGATE PAVING.
5. WHERE CUSTOM FURNITURE IS ACCEPTED BY COUNCIL, IT MUST BE STRUCTURALLY SOUND, MAINTAINABLE AND COMFORTABLE.

6. ALL STAINLESS STEEL WELDS ARE TO BE TIG WELDS, POLISHED SMOOTH AND PICKLED TO REMOVE HEAT TINT.
7. STAINLESS STEEL FRAME TO BE ELECTROPOLISHED UNLESS OTHERWISE APPROVED.
8. CYPRESS PINE IS NOT ACCEPTED.
9. RECYCLED PLASTIC IS A SUPPORTED MATERIAL FOR BATTENS.

E				 <div>ENGINEERING &amp; ASSET SERVICES</div> <div>STANDARD DRAWINGS</div> <div>LANDSCAPE</div>	DRAWING No.	MCCLA 102	DRAWN	S. HUANG	CHECKED	M. HUTCHINSON
D					SCALE		1:25	DATE	03/06/2025	
C					DRAWING NAME	FURNITURE - BENCH	PAPER	A3	REV	B
B	M.H.	3/06/25	PUBLISHED REVISION				SHEET	1	OF	1
A	M.H.	30/01/25	PRELIMINARY FOR REVIEW							
ISSUE	APPROVED	DATE	DETAILS							