



NOTES:

1. GRAVEL PATHS ARE TO BE SECONDARY ACCESS TO RESERVES AND MUST NOT ENCROACH UPON ROOT ZONES OF EXISTING TREES.
2. PATH GRADIENTS IN EXCESS OF 1 IN 33 REQUIRE INDIVIDUAL DESIGN TO AS1428.1 FOR DDA COMPLIANCE.
3. IF THE PATH SLOPES MORE THAN 1:30 THE RATIO OF CEMENT WILL BE 5%.
4. NO LOW POINTS ARE TO BE CREATED ADJACENT TO GRANITIC PATHS.

| | | | | | | | | | | |
|-------|----------|----------|------------------------|--|--------------|-------------------------|-------|------|---------|---------------|
| E | | | |  <div>ENGINEERING & ASSET SERVICES</div> <div>STANDARD DRAWINGS</div> <div>LANDSCAPE</div> | DRAWING No. | MCCLA 201 | DRAWN | Y.SU | CHECKED | M. HUTCHINSON |
| D | | | | | | | SCALE | 1:10 | DATE | 25/06/2025 |
| C | | | | | DRAWING NAME | SURFACE - GRANITIC PATH | PAPER | A3 | REV | B |
| B | M.H. | 25/06/25 | PUBLISHED REVISION | | | | SHEET | 1 | OF | 1 |
| A | M.H. | 30/01/25 | PRELIMINARY FOR REVIEW | | | | | | | |
| ISSUE | APPROVED | DATE | DETAILS | | | | | | | |